

PRACHT®

PRACHT®

LUNA BL



Integrated
Reflector with integrated LED unit

Durable
Impact-resistant polycarbonate casing (IK08)

Solid
High-quality stainless steel clips

Easy Fix
Extremely fast assembly

CASING Polycarbonate, impact-resistant, IK08.
LAMP COVER Polycarbonate with integrated LED unit.
SEALS Age-resistant silicone seals.
ELECTRICAL COMPONENTS High power LED, LED converter.
ASSEMBLY Variable mounting distances with PRACHT-CLIP-SYSTEM. Suitable for ceilings, wall, pendant and rail mounting.
FIELDS OF APPLICATION Parking garages, basements, workshops, 1:1 LL replacement.

Individual luminaire, color temperature 4000 K, Ra>80, IP65

Power	Light distribution	Luminous flux	P/N	Length	Weight
1x22 W	120° wide	2800 lm	5211004	1200 mm	1.8 kg
1x43 W	120° wide	5400 lm	5211014	1200 mm	1.8 kg
1x31 W	120° wide	3800 lm	5211005	1500 mm	2.1 kg
1x52 W	120° wide	6500 lm	5211015	1500 mm	2.1 kg

ACCESSORIES

Through-wiring	P/N
3x1.5 mm² Set LUNA BL 1.2 m, consisting of rigid cable, Terminalblock one-sided	5552132
3x1.5 mm² Set LUNA BL 1.5 m, consisting of rigid cable, Terminalblock one-sided	5552135
5x2.5 mm² Set LUNA BL 1.2 m, consisting of rigid cable, 2x5 pol Terminalblock	5552152
5x2.5 mm² Set LUNA BL 1.5 m, consisting of rigid cable, 2x5 pol Terminalblock	5552155

Protection class I according to EN 60598
 Protection type IP65
 AC 220-240 V 50/60 Hz *registered

ALLROUNDER

EXTREMELY FAST ASSEMBLY
DIFFUSER LUMINAIRE
HIGH QUALITY ENEC
PRICE/PERFORMANCE
DUST-TIGHT HOMOGENEOUS LIGHT
1:1 REPLACEMENT

3
YEAR WARRANTY

50,000 h
OPERATIONAL LIFETIME

ENERGY EFFICIENCY CLASS
A++

IP65

D

-20°C ... +35°C

PRACHT.COM

+49 64 66 / 91 40-0