



BSQ

Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task, accent or general lighting.

Square design with frameless appearance available in several dimensions: 96mm x 96mm, 106mm x 106mm, 161mm x 161mm, 177mm x 177mm, 183mm x 183mm and 203mm x 203mm.

Aluminium body and interior shade powder painted in various finishes, customized RAL under request.

To complete the effect of this fixture, it is also recommended that the interior shade be painted the same RAL colour as the ceiling.

Extensive range of reflectors to achieve the best photometric results.

High-purity aluminium reflector in various finishes: faceted metalized or sandblasted anodised depending on the beam angle outcome.

Remote driver supplied depending on the reference

Passive temperature management: heat dissipation flows through an aluminium heat sink or through heat pipes system.

Ceiling-mounted using galvanised steel support with spring clamps or screws.

Suggested applications: apartments, shops, restaurants, hotels and similar installations.

CRI >80	CRI >90	2700K	3000K	4000K	2700K 6500K	SDCM 3	IP20	A A+
---------	---------	-------	-------	-------	----------------	-----------	------	---------

96mm x 96mm	161mm x 161mm	177mm x 177mm
126mm	169mm	215mm
23° 39°/40° 58°/60°	12°/16° 24°/26° 40°/43° 50°/55°	12°/16° 24°/26° 40°/43° 50°/55°
405lm - 1820lm	1530lm - 7080lm	1530lm - 7080lm
4.1W - 16.3W	11W - 51W	11W - 51W

106mm x 106mm	183mm x 183mm	203mm x 203mm
127mm	176mm	222mm
130mm	219mm	265mm
23° 39°/40° 58°/60°	12° 24° 40° 50°	12° 24° 40° 50°
405lm - 1820lm	1530lm - 2740lm	1530lm - 2740lm
4.1W - 16.3W	2850lm - 3690lm	2850lm - 3690lm
	11W - 17W	11W - 17W
	24W	24W

ELECTRONIC EQUIPMENT

Standard.
1-10V.
DALI/DSI/switchDIM/corridorFUNCTION.
Emergency Kit.
SwitchDIM/ColourSwitch/DALI/DSI.

ACCESSORIES AND FINISHES

+ IP 44	+ ELEC	+ INSTAL	RAL
---------	--------	----------	-----

