



WATERTIGHT

Recessed ceiling-mounted downlights with symmetrical light distribution.

Circular design available in 4 diameters: 165mm, 200mm, 225mm and 250mm.

Protection rating against dust and moisture: entire IP65.
Protection rating for resistance to harmful mechanical impacts: IK07.

High-purity aluminium reflectors available in various finishes: specular anodised, faceted metalized or sandblasted anodised depending on the beam angle outcome.

Aluminium body treated against corrosion and coated with polyester powder painting.

Exterior screws and trim made of 316L stainless steel marine grade.

5mm tempered protection glass clear as standard.

Temperature resistant silicone rubber gasket.

Anti-condensation device.

Remote driver included.

Passive temperature management: heat dissipation through heat pipes.

Mounted to the ceiling by three fixing points.

Suggested applications: white rooms, laboratories, warehouses, leisure areas, service stations, industrial facilities, high humidity outdoor spaces or spaces that require low-maintenance.

CRI >80	CRI >90	2700K	3000K	4000K	SDCM 3	IP65	IK07	A+
---------	---------	-------	-------	-------	--------	------	------	----



ø 165mm			
± 105mm			
12°/16°	24°/26	40°/43°	50°/55°
1530lm - 7080lm			
11W - 51W			



ø 200mm	
± 170mm	± 132mm
17°/21°	39°/42°
1530lm - 7080lm	
11W - 51W	



ø 225mm	
± 194mm	± 159mm
13°/17°	36°/38°
1530lm - 7080lm	
11W - 51W	



ø 250mm	
± 172mm	
37°/38°	
1530lm - 7080lm	
11W - 51W	

ELECTRONIC EQUIPMENT

Standard.

DALI/DSI/switchDIM/corridorFUNCTION.

ACCESSORIES AND FINISHES

+ IK 10	+ ELEC	+ INSTAL	RAL
---------	--------	----------	-----

more product details



rovasi.com



WATERTIGHT SQ

Recessed ceiling-mounted downlights with symmetrical light distribution.

Square design in dimensions 258mm x 258mm and 318mm x 318mm.

Protection rating against dust and moisture: entire IP65.
Protection rating for resistance to harmful mechanical impacts: IK07.

High purity matt anodised aluminium reflector.

Die-cast aluminium body treated against corrosion and coated with polyester powder painting.

5 mm tempered protection glass clear as standard, other finishes under request.

Exterior screws and cover made of 316L stainless steel marine grade.

Temperature resistant silicone rubber gasket.

Anti-condensation device.

Built-in driver, included.

Passive temperature management: heat dissipation through the fixture body itself.

Mounted to the ceiling by four fixing points.

Suggested applications: white rooms, laboratories, porches, shopping malls, warehouses, leisure areas, service stations, industrial facilities, high-humidity outdoor spaces or interior spaces that require low-maintenance.



258mm x 258mm

± 160mm ± 100mm

58° 72°/74°



1530lm - 5560lm

11W - 36W



318mm x 318mm

± 170mm

66°/71°



1530lm - 5560lm

11W - 36W

ELECTRONIC EQUIPMENT

Standard.

DALI/DSI/switchDIM/corridorFUNCTION.

ACCESSORIES AND FINISHES



more product details



rovasi.com



WATERTIGHT SHALLOW

Recessed ceiling-mounted downlights with symmetrical light distribution.

Circular design available in 4 diameters: 165mm, 200mm, 225mm and 250mm.

Remarkable low height: 65mm or 100mm.

Protection rating against dust and moisture: entire IP65.
Protection rating for resistance to harmful mechanical impacts: IK07.

High-purity sandblasted anodised aluminium reflector.

Aluminium body treated against corrosion and coated with polyester powder painting.

5 mm tempered protection glass clear as standard.

Exterior screws and cover made of 316L stainless steel marine grade.

Temperature resistant silicone rubber gasket.

Anti-condensation device.

Remote driver included.

Passive temperature management: heat dissipation through heat pipes or through aluminium heat sink diffuser.

Mounted to the ceiling by three fixing points.

Suggested applications: white rooms, laboratories, porches, shopping malls, warehouses, leisure areas, service stations, industrial facilities, high-humidity outdoor spaces or interior spaces that require low-maintenance. Ceilings with shallow voids.

CRI >80	CRI >90	2700K	3000K	4000K	SDCM 3	IP65	IK07	A+
---------	---------	-------	-------	-------	-----------	------	------	----



ø 165mm

┆ 65mm ┆ 100mm

105° 50°/55°



1530lm - 1980lm 1530lm - 7080lm

11W 11W - 51W



ø 200mm

┆ 65mm ┆ 100mm

112° 77°/79°



1530lm - 2740lm 1530lm - 7080lm

11W - 17W 11W - 51W



ø 225mm

┆ 65mm ┆ 100mm

113° 94°/92°



1530lm - 2740lm 1530lm - 7080lm

11W - 17W 11W - 51W



ø 250mm

┆ 65mm ┆ 100mm

109° 96°/97°



1530lm - 2740lm 1530lm - 7080lm

11W - 17W 11W - 51W

ELECTRONIC EQUIPMENT

Standard.

DALI/DSI/switchDIM/corridorFUNCTION.

ACCESSORIES AND FINISHES



more product
details



rovasi.com