



DAU

Surface mounted downlights with symmetrical light distribution.

Cubic design available in 2 sizes: 212mm x 212mm and 277mm x 277mm.

Protection rating against dust and moisture: entire IP65.
Protection rating for resistance to harmful mechanical impacts: IK07.

Robust body and frame made of die-cast aluminium treated against corrosion and coated with polyester powder painting available in various colour finishes, customized RAL under request.

High-purity matt anodised aluminium reflector.

5mm tempered protection glass clear as standard.

Temperature resistant silicone rubber gasket.

Anti-condensation device.

Built-in driver, included.

Passive temperature management: heat dissipation through the fixture body itself.

Mounting to the ceiling with two securing points in a bracket.
Cable entry from the top of the fixture.

Suggested applications: porches, shopping centres, leisure areas, car parks, service stations, industrial facilities, outdoor ceilings in high humidity areas, or interior spaces that require low-maintenance. Solid ceilings or where there is not space for recessed mounting.



212mm x 212mm

223mm

50°/51° 72°/74°



1850lm - 5560lm

11W - 36W



277mm x 277mm

228mm

62°/63°



1850lm - 7080lm

11W - 51W

ELECTRONIC EQUIPMENT

Standard.

DALI/DSI/switchDIM/corridorFUNCTION.

Emergency Kit.

ACCESSORIES AND FINISHES



more product details



rovasi.com