

NEKO / ROXY
In-track Driver LED Tracklight



ROXY Art
15W 950lm-1000lm

ROXY S
15W 1200lm-1300lm
21W 1600lm-1700lm



ROXY K
28W 2400lm-2600lm



On-Off Version



DALI Dim Version



15W CRI80 2700K 18° 24° 36° 50° 3000K 4000K CITIZEN 50,000H/L20B10 UGR < 19 IP 20 5 GUARANTEED CB CE

15W CRI80 2700K 18° 24° 36° 50° 3000K 4000K CITIZEN 50,000H/L20B10 UGR < 19 IP 20 5 GUARANTEED CB CE DALI 2



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
13 W	15 W	36 V	350 mA	90	2700K	18°	1200lm	900lm	ROA1-9271815F-WB
						24°	1200lm	900lm	ROA1-9272515F-WB
						36°	1200lm	900lm	ROA1-9273615F-WB
						50°	1200lm	900lm	ROA1-9275015F-WB
					3000K	18°	1300lm	950lm	ROA1-9301815F-WB
						24°	1300lm	950lm	ROA1-9302515F-WB
						36°	1300lm	950lm	ROA1-9303615F-WB
						50°	1300lm	950lm	ROA1-9306015F-WB
					4000K	18°	1400lm	1000lm	ROA1-9401815F-WB
						24°	1400lm	1000lm	ROA1-9402515F-WB
						36°	1400lm	1000lm	ROA1-9403615F-WB
						50°	1400lm	1000lm	ROA1-9405015F-WB
13 W	15 W	36 V	350 mA	90	2700K	18°	1200lm	900lm	ROA1-9271815F-BB
						24°	1200lm	900lm	ROA1-9272515F-BB
						36°	1200lm	900lm	ROA1-9273615F-BB
						50°	1200lm	900lm	ROA1-9275015F-BB
					3000K	18°	1300lm	950lm	ROA1-9301815F-BB
						24°	1300lm	950lm	ROA1-9302515F-BB
						36°	1300lm	950lm	ROA1-9303615F-BB
						50°	1300lm	950lm	ROA1-9306015F-BB
					4000K	18°	1400lm	1000lm	ROA1-9401815F-BB
						24°	1400lm	1000lm	ROA1-9402515F-BB
						36°	1400lm	1000lm	ROA1-9403615F-BB
						50°	1400lm	1000lm	ROA1-9405015F-BB

Code Remark: F=(ON-OFF)



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
13 W	15 W	36 V	350 mA	90	2700K	18°	1200lm	900lm	ROA1-9271815D-WB
						24°	1200lm	900lm	ROA1-9272515D-WB
						36°	1200lm	900lm	ROA1-9273615D-WB
						50°	1200lm	900lm	ROA1-9275015D-WB
					3000K	18°	1300lm	950lm	ROA1-9301815D-WB
						24°	1300lm	950lm	ROA1-9302515D-WB
						36°	1300lm	950lm	ROA1-9303615D-WB
						50°	1300lm	950lm	ROA1-9306015D-WB
					4000K	18°	1400lm	1000lm	ROA1-9401815D-WB
						24°	1400lm	1000lm	ROA1-9402515D-WB
						36°	1400lm	1000lm	ROA1-9403615D-WB
						50°	1400lm	1000lm	ROA1-9405015D-WB
13 W	15 W	36 V	350 mA	90	2700K	18°	1200lm	900lm	ROA1-9271815D-BB
						24°	1200lm	900lm	ROA1-9272515D-BB
						36°	1200lm	900lm	ROA1-9273615D-BB
						50°	1200lm	900lm	ROA1-9275015D-BB
					3000K	18°	1300lm	950lm	ROA1-9301815D-BB
						24°	1300lm	950lm	ROA1-9302515D-BB
						36°	1300lm	950lm	ROA1-9303615D-BB
						50°	1300lm	950lm	ROA1-9306015D-BB
					4000K	18°	1400lm	1000lm	ROA1-9401815D-BB
						24°	1400lm	1000lm	ROA1-9402515D-BB
						36°	1400lm	1000lm	ROA1-9403615D-BB
						50°	1400lm	1000lm	ROA1-9405015D-BB

Code Remark: D=(DALI Dim)

Optional accessory



Code for ROA1-9301815D-WB with Honeycomb
ROA1-9301815D-WB-H


Track System



Compatible with GLOBAL / POWERGEAR 3-Circuit Track System




15W 21W CRI90 2700K 3000K 4000K 15° 30° 50° CITIZEN 60,000h@L80B10 UGR < 19 IP 20 5 YEAR WARRANTY CB CE



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code						
13 W	15 W	36 V	350 mA	90	2700K	15°	1400lm	1100lm	ROS1-9271515F-WB						
						30°	1400lm	1100lm	ROS1-9273015F-WB						
						50°	1400lm	850lm	ROS1-9275015F-WB						
						3000K	15°	1500lm	1200lm	ROS1-9301515F-WB					
							30°	1500lm	1200lm	ROS1-9303015F-WB					
							50°	1500lm	900lm	ROS1-9305015F-WB					
						4000K	15°	1600lm	1300lm	ROS1-9401515F-WB					
							30°	1600lm	1300lm	ROS1-9403015F-WB					
							50°	1600lm	1000lm	ROS1-9405015F-WB					
						18 W	21 W	36 V	500 mA	90	2700K	15°	1900lm	1500lm	ROS2-9271521F-WB
												30°	1900lm	1500lm	ROS2-9273021F-WB
												50°	1900lm	1100lm	ROS2-9275021F-WB
3000K	15°	2000lm	1600lm	ROS2-9301521F-WB											
	30°	2000lm	1600lm	ROS2-9303021F-WB											
	50°	2000lm	1200lm	ROS2-9305021F-WB											
4000K	15°	2100lm	1700lm	ROS2-9401821F-WB											
	30°	2100lm	1700lm	ROS2-9403021F-WB											
	50°	2100lm	1300lm	ROS2-9405021F-WB											
13 W	15 W	36 V	350 mA	90	2700K							15°	1400lm	1100lm	ROS1-9271515F-BB
												30°	1400lm	1100lm	ROS1-9273015F-BB
												50°	1400lm	850lm	ROS1-9275015F-BB
						3000K	15°	1500lm	1200lm	ROS1-9301515F-BB					
							30°	1500lm	1200lm	ROS1-9303015F-BB					
							50°	1500lm	900lm	ROS1-9305015F-BB					
						4000K	15°	1600lm	1300lm	ROS1-9401515F-BB					
							30°	1600lm	1300lm	ROS1-9403015F-BB					
							50°	1600lm	1000lm	ROS1-9405015F-BB					
						18 W	21 W	36 V	500 mA	90	2700K	15°	1900lm	1500lm	ROS2-9271521F-BB
												30°	1900lm	1500lm	ROS2-9273021F-BB
												50°	1900lm	1100lm	ROS2-9275021F-BB
3000K	15°	2000lm	1600lm	ROS2-9301521F-BB											
	30°	2000lm	1600lm	ROS2-9303021F-BB											
	50°	2000lm	1200lm	ROS2-9305021F-BB											
4000K	15°	2100lm	1700lm	ROS2-9401821F-BB											
	30°	2100lm	1700lm	ROS2-9403021F-BB											
	50°	2100lm	1300lm	ROS2-9405021F-BB											

Code Remark: F=(ON-OFF)

15W 21W CRI90 2700K 3000K 4000K 15° 30° 50° CITIZEN 60,000h@L80B10 UGR < 19 IP 20 5 YEAR WARRANTY CB CE DALI 2



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code						
13 W	15 W	36 V	350 mA	90	2700K	15°	1400lm	1100lm	ROS1-9271515D-WB						
						30°	1400lm	1100lm	ROS1-9273015D-WB						
						50°	1400lm	850lm	ROS1-9275015D-WB						
						3000K	15°	1500lm	1200lm	ROS1-9301515D-WB					
							30°	1500lm	1200lm	ROS1-9303015D-WB					
							50°	1500lm	900lm	ROS1-9305015D-WB					
						4000K	15°	1600lm	1300lm	ROS1-9401515D-WB					
							30°	1600lm	1300lm	ROS1-9403015D-WB					
							50°	1600lm	1000lm	ROS1-9405015D-WB					
						18 W	21 W	36 V	500 mA	90	2700K	15°	1900lm	1500lm	ROS2-9271521D-WB
												30°	1900lm	1500lm	ROS2-9273021D-WB
												50°	1900lm	1100lm	ROS2-9275021D-WB
3000K	15°	2000lm	1600lm	ROS2-9301521D-WB											
	30°	2000lm	1600lm	ROS2-9303021D-WB											
	50°	2000lm	1200lm	ROS2-9305021D-WB											
4000K	15°	2100lm	1700lm	ROS2-9401821D-WB											
	30°	2100lm	1700lm	ROS2-9403021D-WB											
	50°	2100lm	1300lm	ROS2-9405021D-WB											
13 W	15 W	36 V	350 mA	90	2700K							15°	1400lm	1100lm	ROS1-9271515D-BB
												30°	1400lm	1100lm	ROS1-9273015D-BB
												50°	1400lm	850lm	ROS1-9275015D-BB
						3000K	15°	1500lm	1200lm	ROS1-9301515D-BB					
							30°	1500lm	1200lm	ROS1-9303015D-BB					
							50°	1500lm	900lm	ROS1-9305015D-BB					
						4000K	15°	1600lm	1300lm	ROS1-9401515D-BB					
							30°	1600lm	1300lm	ROS1-9403015D-BB					
							50°	1600lm	1000lm	ROS1-9405015D-BB					
						18 W	21 W	36 V	500 mA	90	2700K	15°	1900lm	1500lm	ROS2-9271521D-BB
												30°	1900lm	1500lm	ROS2-9273021D-BB
												50°	1900lm	1100lm	ROS2-9275021D-BB
3000K	15°	2000lm	1600lm	ROS2-9301521D-BB											
	30°	2000lm	1600lm	ROS2-9303021D-BB											
	50°	2000lm	1200lm	ROS2-9305021D-BB											
4000K	15°	2100lm	1700lm	ROS2-9401821D-BB											
	30°	2100lm	1700lm	ROS2-9403021D-BB											
	50°	2100lm	1300lm	ROS2-9405021D-BB											

Code Remark: D=(DALI Dim)

Optional accessory



Code for ROS1-930 2515D-WB with Honeycomb
ROS1-930 2515D-WB H

Track System





Compatible with GLOBAL / POWERGEAR 3-Circuit Track System

On-Off Version



DALI Dim Version



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
25 W	28 W	36 V	700 mA	90	2700K	20°	2500lm	2000lm	ROK1-9272028F-WB	
						35°	2500lm	2200lm	ROK1-9273528F-WB	
						55°	2500lm	2200lm	ROK1-9275528F-WB	
						3000K	20°	2700lm	2200lm	ROK1-9302028F-WB
							35°	2700lm	2400lm	ROK1-9303528F-WB
							55°	2700lm	2400lm	ROK1-9305528F-WB
					4000K	20°	2900lm	2400lm	ROK1-9402028F-WB	
						35°	2900lm	2600lm	ROK1-9403528F-WB	
						55°	2900lm	2600lm	ROK1-9405528F-WB	



25 W	28 W	36 V	700 mA	90	2700K	20°	2500lm	2000lm	ROK1-9272028D-BB	
						35°	2500lm	2200lm	ROK1-9273528D-BB	
						55°	2500lm	2200lm	ROK1-9275528D-BB	
						3000K	20°	2700lm	2200lm	ROK1-9302028D-BB
							35°	2700lm	2400lm	ROK1-9303528D-BB
							55°	2700lm	2400lm	ROK1-9305528D-BB
					4000K	20°	2900lm	2400lm	ROK1-9402028D-BB	
						35°	2900lm	2600lm	ROK1-9403528D-BB	
						55°	2900lm	2600lm	ROK1-9405528D-BB	

Code Remark: F=(ON-OFF)



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
25 W	28 W	36 V	700 mA	90	2700K	20°	2500lm	2000lm	ROK1-9272028D-WB	
						35°	2500lm	2200lm	ROK1-9273528D-WB	
						55°	2500lm	2200lm	ROK1-9275528D-WB	
						3000K	20°	2700lm	2200lm	ROK1-9302028D-WB
							35°	2700lm	2400lm	ROK1-9303528D-WB
							55°	2700lm	2400lm	ROK1-9305528D-WB
					4000K	20°	2900lm	2400lm	ROK1-9402028D-WB	
						35°	2900lm	2600lm	ROK1-9403528D-WB	
						55°	2900lm	2600lm	ROK1-9405528D-WB	



25 W	28 W	36 V	700 mA	90	2700K	20°	2500lm	2000lm	ROK1-9272028D-BB	
						35°	2500lm	2200lm	ROK1-9273528D-BB	
						55°	2500lm	2200lm	ROK1-9275528D-BB	
						3000K	20°	2700lm	2200lm	ROK1-9302028D-BB
							35°	2700lm	2400lm	ROK1-9303528D-BB
							55°	2700lm	2400lm	ROK1-9305528D-BB
					4000K	20°	2900lm	2400lm	ROK1-9402028D-BB	
						35°	2900lm	2600lm	ROK1-9403528D-BB	
						55°	2900lm	2600lm	ROK1-9405528D-BB	

Code Remark: D=(DALI Dim)

Optional accessory



Code for ROK1-930 3528F-WB with Honeycomb
ROK1-930 3528F-WB H

Track System




Compatible with GLOBAL / POWERGEAR 3-Circuit Track System

NEKO / ROXY-Z
In-track Driver LED Tracklight
Beam Angle Zooming Version



ROXY Art-Z
 15W 1000lm-1200lm
 20°-35° Zooming
 35°-60° Zooming

ROXY S-Z
 15W 1200lm-1400lm
 21W 1600lm-1800lm
 18°-35° Zooming
 35°-60° Zooming



← →
18°-60° Zooming



NEKO / ROXY Art-Z

In-track Driver LED Tracklight
Beam Angle Zooming Version



NEKO / ROXY S-Z

In-track Driver LED Tracklight
Beam Angle Zooming Version



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
13 W	15 W	36 V	350 mA	90	2700K	20°-35°	1200lm	1000lm	ROA1-927Z315F-WB	
						3000K	1300lm	1100lm	ROA1-930Z315F-WB	
						4000K	1400lm	1200lm	ROA1-940Z315F-WB	
2700K	3000K	35°-60°	1200lm	950lm	ROA1-927Z615F-WB	3000K	35°-60°	1300lm	1000lm	ROA1-930Z615F-WB
							4000K	1400lm	1100lm	ROA1-940Z615F-WB

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
13 W	15 W	36 V	350 mA	90	2700K	20°-35°	1200lm	1000lm	ROA1-927Z315F-BB	
						3000K	1300lm	1100lm	ROA1-930Z315F-BB	
						4000K	1400lm	1200lm	ROA1-940Z315F-BB	
2700K	3000K	35°-60°	1200lm	950lm	ROA1-927Z615F-BB	3000K	35°-60°	1300lm	1000lm	ROA1-930Z615F-BB
							4000K	1400lm	1100lm	ROA1-940Z615F-BB

Code Remark: F=(ON-OFF) D=(DALI Dim)

Optional accessory



Code for ROA1-930Z315F-WB with Honeycomb
ROA1-930Z315F-WB H

Honeycomb

Track System



Compatible with GLOBAL / POWERGEAR 3-Circuit Track System.



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
13 W	15 W	36 V	350 mA	90	2700K	18°-35°	1400lm	1200lm	ROS1-927Z315F-WB	
						3000K	1500lm	1300lm	ROS1-930Z315F-WB	
						4000K	1600lm	1400lm	ROS1-940Z315F-WB	
2700K	3000K	35°-60°	1400lm	1100lm	ROS1-927Z615F-WB	3000K	35°-60°	1500lm	1200lm	ROS1-930Z615F-WB
							4000K	1600lm	1300lm	ROS1-940Z615F-WB

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
18 W	21 W	36 V	500 mA	90	2700K	18°-35°	1900lm	1600lm	ROS2-927Z321F-WB	
						3000K	2000lm	1700lm	ROS2-930Z321F-WB	
						4000K	2100lm	1800lm	ROS2-940Z321F-WB	
2700K	3000K	35°-60°	1900lm	1500lm	ROS2-927Z621F-WB	3000K	35°-60°	2000lm	1600lm	ROS2-930Z621F-WB
							4000K	2100lm	1700lm	ROS2-940Z621F-WB

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
13 W	15 W	36 V	350 mA	90	2700K	18°-35°	1400lm	1200lm	ROS1-927Z315F-BB	
						3000K	1500lm	1300lm	ROS1-930Z315F-BB	
						4000K	1600lm	1400lm	ROS1-940Z315F-BB	
2700K	3000K	35°-60°	1400lm	1100lm	ROS1-927Z615F-BB	3000K	35°-60°	1500lm	1200lm	ROS1-930Z615F-BB
							4000K	1600lm	1300lm	ROS1-940Z615F-BB

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
18 W	21 W	36 V	500 mA	90	2700K	18°-35°	1900lm	1600lm	ROS2-927Z321F-BB	
						3000K	2000lm	1700lm	ROS2-930Z321F-BB	
						4000K	2100lm	1800lm	ROS2-940Z321F-BB	
2700K	3000K	35°-60°	1900lm	1500lm	ROS2-927Z621F-BB	3000K	35°-60°	2000lm	1600lm	ROS2-930Z621F-BB
							4000K	2100lm	1700lm	ROS2-940Z621F-BB

Code Remark: F=(ON-OFF) D=(DALI Dim)

Optional accessory



Code for ROS1-930Z315F-WB with Honeycomb
ROS1-930Z315F-WB H

Honeycomb

Track System



Compatible with GLOBAL / POWERGEAR 3-Circuit Track System.