



## OUTDOOR

---

### Bollards

---

#### Colutea

---

- Bollard with 360° light emission, radial beam.
- Bollard head with a diameter of 140mm.
- Protection rating against dust and moisture: IP65 – full protection.
- Protection rating for resistance against harmful mechanical impacts: IK10.
- Die-cast aluminium body and top cover treated for corrosion resistance (nanophoresis) and covered with a polyester powder coating to guarantee durability. Textured paint finish.
- Special coating for environments with very high corrosivity is available under request.
- Extruded aluminium tube with 4 standard heights. Other heights available upon request. Corrosion resistance treatment and finish according to the head finish.
- 7mm opal borosilicate glass.
- Aluminium disks to get specific photometric results and to increase visual comfort.
- Silicone gasket.
- Anticondensation device.
- PCB on the top of the fixture.
- Built-in driver included.
- Pre-wiring with 25cm of 3x1mm<sup>2</sup> cable.
- Double cable gland entry for installation in series.
- IP68 connector not included, it can be ordered separately.
- Mounting plate for floor installation supplied with the fixture.

#### Suggested applications

Pathways, open areas, squares, gardens, promenades, walks.

#### More information





[rovasi.com/en/products/colutea100](https://rovasi.com/en/products/colutea100)

[rovasi.com/en/products/colutea200](https://rovasi.com/en/products/colutea200)

Technical details






Colutea 100



7.2W : min 1070lm <> max 1140lm  
10.6W : min 1450lm <> max 1550lm

Colutea 200



7.2W : min 1070lm <> max 1140lm  
10.6W : min 1450lm <> max 1550lm

Accessories and finishes



On/Off.  
DALI.

Electronic options