




Aerial

Its enormous flexibility enables a larger surface to be covered with a reduced number of structural supports optimising the available space. Luminaires can be positioned exactly where needed, ensuring efficient and functional lighting throughout the environment.

IP65 and IK07 / IK10 pendant downlights. Their robust construction reduces maintenance interventions and ensures reliable operation under demanding environmental conditions.

The catenary mounting system, manufactured from 316L stainless steel, is adjustable to adapt the luminaires to the inclination of the cables.



Ø 120 mm · Ø 180 mm
Ø 235 mm

578lm – 4839lm

13° · 16° · 19° · 24° · 25°
26° · 27° · 35° · 36° · 38°
39° · 77° · 96° · 97° · 109°
112°

CRI>80

2700K · 3000K · 4000K

4,98W – 37,1W

100.000h L90B10

On | Off · DALI-2 · Bluetooth
3 hours battery

➔
Rymdparken
Rågdalen, Sweden



Similar solutions



AERIAL SQ

IP65 Pendant downlights for
catenary systems



SAUCER

IP65 Pendant downlights for
catenary systems



DISTRICT 900

IP65 Pendant linear downlights
for catenary systems



ADHARA OUTDOOR 900

IP65 Pendant downlights
for catenary systems



ALNAIR OUTDOOR 900

IP65 Pendant downlights
for catenary systems



CAPELLA OUTDOOR 900

IP65 Pendant downlights
for catenary systems