




Watertight

An iconic luminaire with pride of place in the outdoor collection. It is recognised for its durability, efficiency and impeccable finishes.

Recessed downlights with symmetrical light distribution designed to offer high-performance accent, workspace or general lighting. They offer complete IP65 protection against dust and moisture while its resistance to mechanical impacts is rated at IK07 or IK10.

They are available in a low height version for installation in very low ceilings, as well as an internally pivoting version of up to 20° for maximum flexibility.



Ø 165 mm	Ø 200 mm	Ø 225 mm	Ø 250 mm
360lm – 6720lm	1085lm – 5737lm	1069lm – 5655lm	1085lm – 6228lm
12° · 16° · 22° · 24° · 26° 35° · 40° · 41° · 43° · 50° 55° · 105°	12° · 16° · 24° · 26° · 39° 40° · 42° · 50° · 77° · 79° 112°	12° · 16° · 24° · 36° · 38° 40° · 50° · 92° · 94° · 113°	12° · 16° · 24° · 26° · 37° 38° · 40° · 43° · 50° · 55° 96° · 97° · 109°
UGR<16 · UGR<19	UGR<16 · UGR<19	UGR<16 · UGR<19	UGR<16 · UGR<19
CRI>80 · CRI>90 R9	CRI>80 · CRI>90 R9	CRI>80 · CRI>90 R9	CRI>80 · CRI>90 R9
2700K · 3000K · 4000K	2700K · 3000K · 4000K	2700K · 3000K · 4000K	2700K · 3000K · 4000K
5,15W – 50,5W	11,9W – 50,5W	11,9W – 50,5W	11,9W – 50,5W
100.000h L90B10	100.000h L90B10	100.000h L90B10	100.000h L90B10
On Off · DALI-2 · 3 hours battery			

Similar solutions



WATERTIGHT SQ
IP65 recessed downlights

Highlights



Fixtures with low depth
(from 65 mm height)



Mall of Emirates VIP car park
Dubai, United Arab Emirates

Reliability over time

Every detail matters to ROVASI for ensuring maximum durability in our luminaires. Particular attention is paid to outdoor solutions, which are designed to withstand the most demanding of conditions. The components, treatments and materials are all selected with the greatest care.

IP68 ventilation valve to reduce condensation.

Aluminium body with C4 anti-corrosion treatment coated in polyester powder.

A4 stainless steel sealing screws as standard.
A2 Vandal-proof stainless steel screws also available as option.

5 mm IK07 tempered protective glass.
IK10 polycarbonate diffuser also available.

Remote driver included and supplied in an IP65 aluminium box.

IP68 cable gland.

IP68 cable gland.

316L Stainless steel trim.

Temperature-resistant silicone rubber gasket.

316L stainless steel trim available in a painted finish

At ROVASI, we only work with materials that guarantee maximum durability. In the case of stainless steel, our luminaires are made from 316L stainless steel. This material is recognised for its exceptional ability to resist corrosion, even in the most demanding environments.

For seamless integration into the architecture, the trim and sealing screws can also be painted in the same colour as the surrounding environment to guarantee total visual harmony and an absolutely impeccable finish.



RAL 9010



RAL 9006



RAL 9005

↗
Special Forces Complex
Al Khoud, Oman

