SUGAR - SM – Ceiling Light System



90° | 2700K 3000K 4000K | Tunable White | CRI >80 | CRI >90 | UGR<19 | IP40 | CE | CB | UKCA | Intertek | 5 YEARS GUARANTEE

Quick Info

- LED: 16W, 24W, 46W, 60W, CRI>80, CRI>90
- CCT: 2700K, 3000K, 4000K Available as Standard
- Beam Angle: 90°
- Lumen Output: Up to 8700lm System Luminous Flux
- IP Class: IP40 from Front
- LED Driver: On-Off, Phase Dim, 1-10V Dim, DALI Dim

Light Distribution







Order Info (Surface/ Wall Mounted SUGAR 350 in Black -Gold Finish as an Example)

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
16W	18W	34V	500mA	80	2700K	90°	2500lm	2000lm	S3SM-8279016F-BG-AC
					3000K	90°	2700lm	2150lm	S3SM-8309016F-BG-AC
					4000K	90°	2900lm	2350lm	S3SM-8409016F-BG-AC
24W	26W	34V	700mA	80	2700K	90°	3500lm	3000lm	S4SM-8279024F-BG-AC
					3000K	90°	3700lm	3150lm	S4SM-8309024F-BG-AC
					4000K	90°	4000lm	3400lm	S4SM-8409024F-BG-AC
46W	50W	34V	1400mA	80	2700K	90°	7200lm	5850lm	S6SM-8279046F-BG-AC
					3000K	90°	8100lm	6150lm	S6SM-8309046F-BG-AC
					4000K	90°	8600lm	6700lm	S6SM-8409046F-BG-AC
60W	62W	43V	1400mA	80	2700K	90°	9900lm	7500lm	S9SM-8279060F-BG-AC
					3000K	90°	10500lm	7900lm	S9SM-8309060F-BG-AC
					4000K	90°	11000lm	8700lm	S9SM-8409060F-BG-AC

Code Remark: N=N(ON Driver) F=F(ON-OFF) A=A(1-10V Dim) D=D(DALI Dim)

Acoustic colours

NKA-01 Papyrus white | NKA-03 Pearl dark grey | NKA-06 Honey yellow | NKA-08 Capn blue | NKA-11 Signal black

Luminaire colours

Coding

S9SM*** – *** ** ** * – ** – *

Model	CRI/ CCT	Beam Angle	LED Power	Control	Finish	Acoustic
S9SM SUGAR 900 Surface/ Wall Mounted	**827** CRI80/ 2700K	**90** 90°	**16** 16W	**N** ONo Driver	**WW** White-White	
	830 CRI80/ 3000K		**24** 24W	**F** On-Off	**BB** Black-Black	
	840 CRI80/ 4000K		**46** 46W	**A** 1-10V Dim	**BG** Black-Gold	
	927 CRI90/ 2700K		**60** 60W	**D** DALI Dim	**WG** White-Gold (Optional)	
	930 CRI90/ 3000K					
	940 CRI90/ 4000K					

SUGAR - PR – Pendant Direct Linear System





Acoustic colours

NKA-01 Papyrus white
NKA-03 Pearl dark grey
NKA-06 Honey yellow
NKA-08 Capn blue
NKA-11 Signal black

Luminaire colours

90° | 2700K 3000K 4000K | Tunable White | CRI >80 | CRI >90 | UGR<19 | IP40 | CE | CB | UK CA | ETL Intertek | 5 YEARS GUARANTEE

Quick Info

- LED: 16W, 24W, 46W, 60W, CRI>80, CRI>90
- CCT: 2700K, 3000K, 4000K Available as Standard, Tunable White Available
- Beam Angle: 90°
- Lumen Output: Up to 8700lm System Luminous Flux
- IP Class: IP40 from Front
- LED Driver: On-Off, Phase Dim, 1-10V Dim, DALI Dim

Light Distribution







Order Info (Surface/ Wall Mounted SUGAR 350 in Black -Gold Finish as an Example)

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
16W	18W	34V	500mA	80	2700K	90°	2500lm	2000lm	S3PR-8279016N-BG-AC
					3000K	90°	2700lm	2150lm	S3PR-8309016N-BG-AC
					4000K	90°	2900lm	2350lm	S3PR-8409016N-BG-AC
24W	26W	34V	700mA	80	2700K	90°	3500lm	3000lm	S4PR-8279024N-BG-AC
					3000K	90°	3700lm	3150lm	S4PR-8309024N-BG-AC
					4000K	90°	4000lm	3400lm	S4PR-8409024N-BG-AC
46W	50W	34V	1400mA	80	2700K	90°	7200lm	5850lm	S6PR-8279046N-BG-AC
					3000K	90°	8100lm	6150lm	S6PR-8309046N-BG-AC
					4000K	90°	8600lm	6700lm	S6PR-8409046N-BG-AC
60W	62W	43V	1400mA	80	2700K	90°	9900lm	7500lm	S9PR-8279060N-BG-AC
					3000K	90°	10500lm	7900lm	S9PR-8309060N-BG-AC
					4000K	90°	11000lm	8700lm	S9PR-8409060N-BG-AC

Code Remark: N=N(ON Driver) F=F(ON-OFF) A=A(1-10V Dim) D=D(DALI Dim)

Coding

S9PR*** – *** ** ** * – ** – *

Model	CRI/ CCT	Beam Angle	LED Power	Control	Finish	Acoustic
S9PR SUGAR 900 Pendant Rod	**827** CRI80/ 2700K	**90** 90°	**16** 16W	**N** ONo Driver	**WW** White-White	
	830 CRI80/ 3000K		**24** 24W	**F** On-Off	**BB** Black-Black	
	840 CRI80/ 4000K		**46** 46W	**A** 1-10V Dim	**BG** Black-Gold	
	927 CRI90/ 2700K		**60** 60W	**D** DALI Dim	**WG** White-Gold (Optional)	
	930 CRI90/ 3000K					
	940 CRI90/ 4000K					

SUGAR - PW – Pendant Direct Linear System





Acoustic colours

NKA-01 Papyrus white
NKA-03 Pearl dark grey
NKA-06 Honey yellow
NKA-08 Capn blue
NKA-11 Signal black

Luminaire colours

90° | 2700K 3000K 4000K | Tunable White | CRI >80 | CRI >90 | UGR<19 | IP40 | CE | CB | UKCA | ETL Intertek | 5 YEARS GUARANTEE

Quick Info

- LED: 16W, 24W, 46W, 60W, CRI>80, CRI>90
- CCT: 2700K, 3000K, 4000K Available as Standard, Tunable White Available
- Beam Angle: 90°
- Lumen Output: Up to 8700lm System Luminous Flux
- IP Class: IP40 from Front
- LED Driver: On-Off, Phase Dim, 1-10V Dim, DALI Dim

Light Distribution







Order Info (Surface/ Wall Mounted SUGAR 350 in Black -Gold Finish as an Example)

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
16W	18W	34V	500mA	80	2700K	90°	2500lm	2000lm	S3PW-8279016N-BG
					3000K	90°	2700lm	2150lm	S3PW-8309016N-BG
					4000K	90°	2900lm	2350lm	S3PW-8409016N-BG
24W	26W	34V	700mA	80	2700K	90°	3500lm	3000lm	S4PW-8279024N-BG
					3000K	90°	3700lm	3150lm	S4PW-8309024N-BG
					4000K	90°	4000lm	3400lm	S4PW-8409024N-BG
46W	50W	34V	1400mA	80	2700K	90°	7200lm	5850lm	S6PW-8279046N-BG
					3000K	90°	8100lm	6150lm	S6PW-8309046N-BG
					4000K	90°	8600lm	6700lm	S6PW-8409046N-BG
60W	62W	43V	1400mA	80	2700K	90°	9900lm	7500lm	S9PW-8279060N-BG
					3000K	90°	10500lm	7900lm	S9PW-8309060N-BG
					4000K	90°	11000lm	8700lm	S9PW-8409060N-BG

Code Remark: N=N(ON Driver) F=F(ON-OFF) A=A(1-10V Dim) D=D(DALI Dim)

Coding

S9PW*** – *** ** ** * – ** – *

Model	CRI/ CCT	Beam Angle	LED Power	Control	Finish	Acoustic
S9PW SUGAR 900 Pendant Rod	**827** CRI80/ 2700K	**90** 90°	**16** 16W	**N** ONo Driver	**WW** White-White	
	830 CRI80/ 3000K		**24** 24W	**F** On-Off	**BB** Black-Black	
	840 CRI80/ 4000K		**46** 46W	**A** 1-10V Dim	**BG** Black-Gold	
	927 CRI90/ 2700K		**60** 60W	**D** DALI Dim	**WG** White-Gold (Optional)	
	930 CRI90/ 3000K					
	940 CRI90/ 4000K					